

Collection of recessed downlights for architectural applications[1]. Excellent build quality with features for the most demanding professional applications. Available in 2 apertures with complete light distributions offering fixed, adjustable and wall washer optics. Generous light outputs with excellent chromatic performance and enhanced visual comfort (up to UGR<10). Also available with a Safety glass with a sealing system to increase the IP rating (IP65).

(1) Related products in the same family for other sizes: Laser 17, Laser 25, Laser 38 and Laser 96.

Optic type	Optic	Load (W)	Lumens (lm)	Efficacy (lm/W)	Max Candela (cd)
Comfort Fixed	26°	10.5W	986	94	4 183
	46°		1 011	96	1 981
	56°		1 012	96	1 344
Comfort Adjustable	16°	10.5W	948	90	6 149
	26°		973	93	4 232
	44°		986	94	1 973
Super Comfort Fixed	26°	10.5W	986	94	4 295
	44°		1 026	98	2 084
	56°		1 000	95	1 343
Super Comfort Adjustable	14°	8W	591	74	5 646
	24°		656	82	3 450
	39°		648	81	1 595
Wall washer		10.5W	700	67	506

Source: COB LED module
2700K: 90CRI
3000K: 90CRI
3500K: 90CRI
4000K: 90CRI

Lumen maintenance: 90% of initial lumens at 50 000 hours (L90, LM-80)

Optic: Visual comfort:
- UGR<13 (Comfort)
- UGR<10 (Super Comfort)

Fixed: Deep recessed reflector available with medium, wide flood or very wide flood optic.
Adjustable: Deep recessed reflector available with spot, medium, flood or wide flood optic.
Optical assembly hot-aiming adjustment.
- Comfort optic type: 30° tilt
- Super comfort optic type: 30° tilt and 355°pan

Wall washer: Wall washer with lens.

Material: *Body:* Die-cast aluminum optical assembly
Reflector: Metalized polycarbonate
Baffle: Painted thermoplastic
Housing: Galvanized steel

Mounting: Cut-out Ø3" (Ø75mm)
New construction with housing suitable for airtight applications (See page 6 for details)

Electrical: High efficiency dimmable LED driver, rated at 50 000 hours. See remote LED driver options.

Finish: Powder coated body and painted metallized baffle (See page 2 for details)

Weight: Trim: 0.57lb (0.26kg)
Trimless: 0.29lb (0.13kg)

Warranty: 5 year limited warranty

Rating: IP20, IP44 (under the ceiling for trim fixed)
IP23 (under the ceiling for trim adjustable)
IP65 (under the ceiling, see page 2 for availability)

Certification: cULus listed for damp location. Interior use only.

Title 24-JA8-2019 high efficiency luminaire. Airtight luminaire less than 2 cfm leakage @1.57PSI per ASTM E283. To confirm which versions are certified, please consult the product list: https://cacertappliances.energy.ca.gov/Pages/Search/AdvancedSearch.aspx

ORDERING INFO

CLICK HERE

CONFIGURE

ILAS75RAT-REM
PRODUCT CODE

INSTALLATION CODE

R		AT				REM	
SHAPE	**MOUNTING**	**INSTALLATION**	**LED**	**OPTIC TYPE**	**OPTIC**	**VOLTAGE**	**FINISH** (trim finish / baffle finish)
R Round	**T** Trim **L** Trimless	**AT** Airtight housing	**927** 2700K, 90CRI **930** 3000K, 90CRI **935** 3500K, 90CRI **940** 4000K, 90CRI	**SGF** [1] Comfort fixed **SGA** [1] Comfort adjustable **SCF** Super comfort fixed **SCA** Super comfort adjustable **FWW** [2] Fixed wall washer **WGF** [1] [3] Comfort fixed IP65	**SP** [4] Spot (16° / 14°) **MD** Medium (26° / 24°) **FL** [5] Flood (39°) **WF** [6] Wide flood (46° / 44°) **VW** [7] Very wide flood (56°)	**REM** Remote	*TRIM* **01** White / black **02** Black / black **31** White / white **41** * White / gold **E4** * White / chrome **E7** * White / black chrome **E9** * White / gold matte *TRIMLESS* **31** White **02** Black **04** * Chrome **14** * Gold **E6** * Black chrome **E8** * Gold matte

(1) Available with trim (**T**) mounting.
(2) No optic selection necessary when ordering the fixed wall washer (**FWW**) optic type.
(3) Available with 2700K, 90CRI (**927**) LED for wide flood (**WF**) optic.
(4) Available for adjustable (**SGA**, **SCA**) optic type.
(5) Available for super comfort adjustable (**SCA**) optic type.
(6) Available for comfort (**SGF**, **SGA**, **WGF**) optic type. Also available for super comfort fixed (**SCF**) optic type.
(7) Available for fixed (**SGF**, **SCF**) optic type.

* May require a longer lead time than standard. Please contact customer service for details.

iGuzzini
9320 Boul. St-Laurent, suite 100, Montréal (Québec) Canada H2N 1N7, P.: 514.523.1339 F.: 514.525.6107 www.iguzzini-na.com

REMOTE LED DRIVER OPTIONS (TO BE ORDERED SEPARATELY)

ILAS75RAT-REM
PRODUCT CODE

Indoor rated drivers

Driver box model	Min-max units	
	LASER 75 **10.5W***	**LASER 75** (Only for Super Comfort Adjustable) **8W***
4444-0300-012-UNV-ED10	1	
4444-0300-012-UNV-SD10	1	
4444-0300-012-UNV-EDA	1	
4444-0300-012-UNV-SDA	1	
4444-0200-008-UNV-ED10		1
4444-0200-008-UNV-SD10		1
4444-0200-008-UNV-EDA		1
4444-0200-008-UNV-SDA		1

* Wattage requirement for one (1) fixture (remote fixture only).

DRIVER BOX MODEL DESCRIPTION

DIMENSION	CONSTANT CURRENT	WATTAGE	VOLTAGE	DIMMING PROTOCOL[1]
4444 6" x 4" x 3" (152 x 102 x 76mm)	**0200** 200mA **0300** 300mA	**008 to 012** 8W to 12W	**UNV** 120-277V	**ED10** [2] 0-10V eldoLED ECOdrive Max distance: 9m (30ft) [3] (down to 1%) **SD10** [2] 0-10V eldoLED SOLOdrive Max distance: 9m (30ft) [3] (down to 0.1%) **EDA** [2] DALI eldoLED ECOdrive Max distance: 9m (30ft) [3] (down to 1%) **SDA** [2] DALI eldoLED SOLOdrive Max distance: 9m (30ft) [3] (down to 0.1%)

WIRING DIAGRAMS



(1) Dimming levels will vary depending on the dimmer used and the number of luminaires on the line.

(2) May require a longer lead time than standard. Please contact customer service for details.

(3) Max distance cable calculated for 16AWG cable. Contact customer service for longer remote distance

TRIM MODELS DIMENSIONS

FIXED OPTIC

COMFORT	SUPER COMFORT	WALL WASHER



FRONT VIEW



BOTTOM VIEW

ADJUSTABLE OPTIC

COMFORT	SUPER COMFORT



FRONT VIEW

BOTTOM VIEW

TRIMLESS MODELS DIMENSIONS

FIXED OPTIC

SUPER COMFORT



WALL WASHER



FRONT VIEW



BOTTOM VIEW

ADJUSTABLE OPTIC

SUPER COMFORT



FRONT VIEW

BOTTOM VIEW

INSTALLATION

New construction with airtight (AT) housing

Housing with hanger bars system for new construction installations.
Suitable for insulated ceiling, chicago plenum and airtight applications.
Housing can be shipped seperately.

Ceiling thickness:
Trim: 1/8" to 7/8" (3mm - 22mm)
Trimless: 1/2" to 15/16" (12.5mm - 24mm)

Total weight:
Trim: 6.33lb (2.87kg)
Trimless: 6.17lb (2.8 kg)

Hanger bars suitable for Grid ceiling





*Provide a minimum of 1 1/16" (46mm) on each side for the hanger bar fixations

Model	Housing	Cut-out dimensions	Cut-out position (A)	Max Overall dimensions (B*xC*)	Hanger bars (D)	Clearance (H)
LASER 75	BI-LAS75-RT-AT-REM	Ø 3" (Ø 75mm)	6 7/16" (164mm)	12 1/4" x 12 15/16" (311 x 328mm)	14 1/4" to 26" (362 to 660mm)	4" (102mm)
	BI-LAS75-RLF-AT-REM					
	BI-LAS75-RLA-AT-REM					

ACCESSORIES (TO BE ORDERED SEPARATELY)

Fixture can hold a maximum of 3 accessories at a time.

RESET

	PRODUCT CODE	COMFORT FIXED (SGF)	COMFORT ADJUSTABLE (SGA)	SUPER COMFORT FIXED (SCF)	SUPER COMFORT ADJUSTABLE (SCA)	COMFORT FIXED IP65 (WGF)
HONEYCOMB LOUVRE	**IMY11-04 -** Black				☐	
	IMY22-04 - Black	☐	☐	☐		☐
DIFFUSER GLASS	**IMY12-65 -** Nitric				☐	
	IMY23-65 - Nitric	☐	☐	☐		
REFRACTOR LENS (for elliptical distribution)	**IMY13-24 -** Clear transparent				☐	
	IMY24-24 - Clear transparent	☐	☐	☐		☐
DECORATIVE RINGS	**IMY15-05 -** Red				☐	
	IMY15-06 - Yellow				☐	
	IMY15-16 - Blue				☐	
	IMY26-05 - Red		☐	☐		☐
	IMY26-06 - Yellow		☐	☐		☐
	IMY26-16 - Blue		☐	☐		☐
INTERNAL ANTI-GLARE RING	**IMY27-04 -** Black		☐			
DECORATIVE CYLINDERS	**IMY28-05 -** Red	☐				☐
	IMY28-06 - Yellow	☐				☐
	IMY28-16 - Blue	☐				☐
	IMY28-24 - Clear transparent	☐				☐

PHOTOMETRIC DATA

COMFORT
FIXED

CCT (K)	CRI	LOAD (W)*	OPTIC	LUMENS (lm)	EFFICACY (lm / W)	MAX CANDELA (cd)	MODELS
3000K	90	10.5W	Medium 26°	986	94	4 183	ILAS75RXXX-930-SGFMD
			Wide flood 46°	1 011	96	1 981	ILAS75RXXX-930-SGFWF
			Very wide flood 56°	1 012	96	1 344	ILAS75RXXX-930-SGFVW

*For products that uses a remote led driver, total system wattage will varies according to the efficacy of the remote led driver selected. For this reason, the load and efficacy values given in the table above refers to the led source only and does not include the led driver consumption.
Use multiplier table for other CCT and CRI output data. Efficacy based on IESNA LM-79 test reports.

Medium 26° (3000K, 90CRI)



	Center beam fc	Beam width ft
2ft	1 046	0.9
4ft	261	1.9
6ft	116	2.8
8ft	65.4	3.7
10ft	41.8	4.7
12ft	29	5.6

Wide flood 46° (3000K, 90CRI)



	Center beam fc	Beam width ft
2ft	491	1.6
4ft	123	3.1
6ft	54.5	4.7
8ft	30.7	6.2
10ft	19.6	7.8
12ft	13.6	9.3

Very wide flood 56° (3000K, 90CRI)



	Center beam fc	Beam width ft
2ft	329	2.0
4ft	82.3	4.1
6ft	36.6	6.1
8ft	20.6	8.2
10ft	13.2	10.2
12ft	9.15	12.3

COMFORT
ADJUSTABLE

CCT (K)	CRI	LOAD (W)*	OPTIC	LUMENS (lm)	EFFICACY (lm / W)	MAX CANDELA (cd)	MODELS
3000K	90	10.5W	Spot 16°	948	90	6 149	ILAS75RXXX-930-SGASP
			Medium 26°	973	93	4 232	ILAS75RXXX-930-SGAMD
			Wide flood 44°	986	94	1 973	ILAS75RXXX-930-SGAWF

*For products that uses a remote led driver, total system wattage will varies according to the efficacy of the remote led driver selected. For this reason, the load and efficacy values given in the table above refers to the led source only and does not include the led driver consumption.
Use multiplier table for other CCT and CRI output data. Efficacy based on IESNA LM-79 test reports.

Spot 16° (3000K, 90CRI)



	Center beam fc	Beam width ft
2ft	1 537	0.6
4ft	384	1.1
6ft	171	1.7
8ft	96.1	2.3
10ft	61.5	2.9
12ft	42.7	3.4

Medium 26° (3000K, 90CRI)



	Center beam fc	Beam width ft
2ft	1 058	0.9
4ft	265	1.8
6ft	118	2.7
8ft	66.1	3.7
10ft	42.3	4.6
12ft	29.4	5.5

Wide flood 44° (3000K, 90CRI)



	Center beam fc	Beam width ft
2ft	493	1.6
4ft	123	3.3
6ft	54.8	4.9
8ft	30.8	6.5
10ft	19.7	8.1
12ft	13.7	9.8

CCT options	2700K	3000K	3500K	4000K
CRI options	90CRI	90CRI	90CRI	90CRI
Multiplier	**0.96**	**1**	**1.04**	**1.07**

iGuzzini
9320 Boul. St-Laurent, suite 100, Montréal (Québec) Canada H2N 1N7, P.: 514.523.1339 F.: 514.525.6107 www.iguzzini-na.com

PHOTOMETRIC DATA

SUPER COMFORT FIXED

CCT (K)	CRI	LOAD (W)*	OPTIC	LUMENS (lm)	EFFICACY (lm / W)	MAX CANDELA (cd)	MODELS
3000K	90	10.5W	Medium 26°	986	94	4 295	ILAS75RXXX-930-SCFMD
			Wide flood 44°	1 026	98	2 084	ILAS75RXXX-930-SCFWF
			Very wide flood 56°	1 000	95	1 343	ILAS75RXXX-930-SCFVW

*For products that uses a remote led driver, total system wattage will varies according to the efficacy of the remote led driver selected. For this reason, the load and efficacy values given in the table above refers to the led source only and does not include the led driver consumption.
Use multiplier table for other CCT and CRI output data. Efficacy based on IESNA LM-79 test reports.

Medium 26° (3000K, 90CRI)



	Center beam fc	Beam width ft
2ft	1 074	0.9
4ft	268	1.8
6ft	119	2.8
8ft	67.1	3.7
10ft	43	4.6
12ft	29.8	5.5

Wide flood 44° (3000K, 90CRI)



	Center beam fc	Beam width ft
2ft	521	1.6
4ft	130	3.3
6ft	57.9	4.9
8ft	32.6	6.5
10ft	20.8	8.1
12ft	14.5	9.8

Very wide flood 56° (3000K, 90CRI)



	Center beam fc	Beam width ft
2ft	328	2.1
4ft	82.1	4.1
6ft	36.5	6.2
8ft	20.5	8.2
10ft	13.1	10.3
12ft	9.12	12.3

SUPER COMFORT ADJUSTABLE

CCT (K)	CRI	LOAD (W)*	OPTIC	LUMENS (lm)	EFFICACY (lm / W)	MAX CANDELA (cd)	MODELS
3000K	90	7.5W	Spot 14°	591	79	5 646	ILAS75RXXX-930-SCASP
			Medium 24°	656	87	3 450	ILAS75RXXX-930-SCAMD
			Flood 39°	648	86	1 595	ILAS75RXXX-930-SCAFL

*For products that uses a remote led driver, total system wattage will varies according to the efficacy of the remote led driver selected. For this reason, the load and efficacy values given in the table above refers to the led source only and does not include the led driver consumption.
Use multiplier table for other CCT and CRI output data. Efficacy based on IESNA LM-79 test reports.

Spot 14° (3000K, 90CRI)



	Center beam fc	Beam width ft
2ft	1 412	0.4
4ft	353	0.9
6ft	157	1.3
8ft	88.2	1.8
10ft	56.5	2.2
12ft	39.2	2.7

Medium 24° (3000K, 90CRI)



	Center beam fc	Beam width ft
2ft	863	0.8
4ft	216	1.6
6ft	95.8	2.5
8ft	53.9	3.3
10ft	34.5	4.1
12ft	24	4.9

Flood 39° (3000K, 90CRI)



	Center beam fc	Beam width ft
2ft	399	1.4
4ft	99.7	2.8
6ft	44.3	4.2
8ft	24.9	5.6
10ft	16	7.0
12ft	11	8.5

CCT options	2700K	3000K	3500K	4000K
CRI options	90CRI	90CRI	90CRI	90CRI
Multiplier	**0.96**	**1**	**1.04**	**1.07**

PHOTOMETRIC DATA

WALL WASHER

CCT (K)	CRI	LOAD (W)*	OPTIC	LUMENS (lm)	EFFICACY (lm / W)	MAX CANDELA (cd)	MODELS
3000K	90	10.5W	Wall washer	700	67	506	ILAS75RXXX-930-FWW

*For products that uses a remote led driver, total system wattage will varies according to the efficacy of the remote led driver selected. For this reason, the load and efficacy values given in the table above refers to the led source only and does not include the led driver consumption.
Use multiplier table for other CCT and CRI output data. Efficacy based on IESNA LM-79 test reports.

Wall washer (3000K, 90CRI)



CCT options	2700K	3000K	3500K	4000K
CRI options	90CRI	90CRI	90CRI	90CRI
Multiplier	**0.96**	**1**	**1.04**	**1.07**

LED COLOR FIDELITY DATA

COMFORT • FIXED / ADJUSTABLE
SUPER COMFORT • FIXED
WALL WASHER

CRI	CCT	R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15	Rf	Rg	Melanopic ratio
90	2700K	93	96	97	93	92	95	93	83	62	89	93	83	93	98	89	92	100	0.478
	3000K	93	95	96	94	93	94	94	86	67	88	94	80	94	97	91	92	100	0.547
	3500K	93	95	95	93	92	93	95	87	67	86	93	75	93	97	91	91	100	0.625
	4000K	92	94	95	92	91	92	95	86	64	85	91	70	92	97	90	90	98	0.718

SUPER COMFORT • ADJUSTABLE

CRI	CCT	R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15	Rf	Rg	Melanopic ratio
90	2700K	94	98	99	95	95	98	90	79	54	94	98	90	95	100	88	93	99	0.492
	3000K	95	97	98	96	95	96	93	84	62	92	97	86	95	98	90	93	101	0.555
	3500K	93	96	98	94	93	95	93	82	57	90	95	79	94	98	89	92	98	0.640
	4000K	92	95	96	92	91	93	93	83	57	87	93	73	93	98	89	91	98	0.725