


Elegant LED profile system with small aperture, only 1¼". Available in two different heights. Modular continuous systems configured to obtain bespoke solutions by incorporating Laser Blade XS modules from iGuzzini. Available as single modules or continuous runs.

Luminaire characteristics:


Power input: 13.5W to 34.5W per module
Lumens: 291lm to 2241lm per module (3000K, 90CRI)
Luminaire efficacy: Up to 64lm/W

Source:	White LED (LM-80) 2700K: 90CRI, 3000K: 90CRI, 3500K: 90CRI, 4000K: 90CRI.
Lumen maintenance:	80% of initial lumens at 50 000 hours (L80) (LM-79).
Optics:	Medium, flood, wide flood, wall washer or wall washer LGC.
Material:	Profile: Extruded aluminum, End caps: Die-cast aluminum, Cover plate: Extruded aluminum, Canopy: Aluminum, Baffles and reflector: Thermoplastic, Wall washer diffuser: PMMA ribbed acrylic.
Mounting:	Surface mounted using anchoring screws. Installs onto a standard 4" octagonal junction box. Supplied with square canopy.
Electrical:	Integral high efficiency LED driver, rated at 50 000 hours, 120-277V.
Dimming:	0-10V (120-277V), down to 1%. Leading edge (TRIAC) and trailing edge (ELV) (120V only), down to 10%.
Finish:	Available in white RAL9010 or black RAL9004. The canopy is supplied white.
Weight:	Max: 1.19 lbs/ft (0.54kg/ft)
Warranty:	5 year limited warranty.
Ratings:	IP20
Certification:	 cULus listed for damp location. Interior use only.

HIGH PROFILE (3454)



COMPACT PROFILE (3464)



ORDERING INFO

- - - -
FIXTURE

MODEL

☐ 3454 - High profile - 3 3/8" (85mm) ☐ 3464 - Compact profile - 2 13/16" (72mm)

LENGTH

The luminaire row must be ordered by 4' increments.

CONFIGURATION

☐ A1 - 48" spacing ☐ A2 - 24" spacing

LASER BLADE XS MODEL

☐ LBXS05 - 5 Cells⁽¹⁾ ☐ LBXS10 - 10 Cells ☐ LBX15 - 15 Cells

LED

☐ 927 - 2700K, 90CRI ☐ 930 - 3000K, 90CRI ☐ 935 - 3500K, 90CRI ☐ 940 - 4000K, 90CRI

DIRECT OPTIC

☐ MD - Medium 24° ☐ FL - Flood 41° ☐ WF - Wide flood 58° ☐ WW - Wall washer ☐ WL - Wall washer LGC (longitudinal glare control)


WALL WASHER DIRECTION (FEED POSITION)

☐ L - Left feed ☐ R - Right feed ☐ N - Not applicable⁽²⁾

VOLTAGE

☐ UNV - 120-277V ☐ 120 - 120V

FINISH (profile finish / cover plate finish / baffle finish)



☐ 21 - White / black / black  ☐ 02 - Black / black / black 
☐ 01 - White / white / black 

DIMMING


☐ D01 - 0-10V (down to 1%)⁽³⁾ ☐ LTE - Leading and trailing edge (120V only) (down to 10%)

⁽¹⁾ Available with 24" spacing (A2) configuration.
⁽²⁾ Available for medium (MD), flood (FL), wide flood (WF) optics.
⁽³⁾ Available with 120-277V (UNV) voltage.


WALL WASHER DIRECTION (FEED POSITION)




DIMENSION AND CONFIGURATION




INLINE UNIT CONFIGURATION WITH LASER BLADE XS 5 CELLS (**LBXS05**)
 Downlight, general light or wall washer




INLINE UNIT CONFIGURATION WITH LASER BLADE XS 10 CELLS (**LBXS10**)
 Downlight, general light or wall washer



INLINE UNIT CONFIGURATION WITH LASER BLADE XS 15 CELLS (**LBXS15**)
 Downlight, general light or wall washer



CONTINUOUS ROW EXAMPLE
 Inline units can be combined to obtain a linear continuous row.




LED COLOR FIDELITY DATA

CCT	R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15	Rf	Rg	Melanopic ratio
2700K	94	94	91	93	93	92	93	88	70	84	94	82	94	94	92	88	104	0.456
3000K	97	96	93	94	96	94	95	92	82	89	94	86	97	95	96	90	104	0.538
3500K	99	99	98	98	98	97	97	96	93	99	99	83	99	98	98	92	99	0.666
4000K	94	94	93	94	92	91	97	91	74	85	91	72	93	96	92	91	99	0.744

PHOTOMETRIC DATA

Photometric data for one laser blade module


LBXS05




CCT (K)	CRI	LOAD (W)	OPTIC	LUMENS (lm)	EFFICACY (lm / W)	MAX CANDELA (cd)	MODELS
3000K	90	13.5W	Medium 24°	695	51	3 212	LBXS05-930-MD
			Flood 41°	730	54	1 500	LBXS05-930-FL
			Wide flood 58°	730	54	930	LBXS05-930-WF
			Wall washer	345	25	259	LBXS05-930-WW
			Wall washer LGC (longitudinal glare control)	291	21	287	LBXS05-930-WL

Use multiplier table for other CCT and CRI output data. Efficacy based on IESNA LM-79 test reports. Visit iguzzini.com/us for complete photometric data.


Medium 24° (3000K, 90CRI)




Flood 41° (3000K, 90CRI)




Wide flood 58° (3000K, 90CRI)



Wall washer (3000K, 90CRI)



Wall washer LGC (3000K, 90CRI)




CCT options	2700K	3000K	3500K	4000K
CRI options	90CRI	90CRI	90CRI	90CRI
Multiplier	0.95	1	1	1.21

PHOTOMETRIC DATA

Photometric data for one laser blade module

LBXS10




MD
FL
WF


CCT (K)	CRI	LOAD (W)	OPTIC	LUMENS (lm)	EFFICACY (lm / W)	MAX CANDELA (cd)	MODELS
3000K	90	23.8W	Medium 24°	1 422	59	6 570	LBXS10-930-MD
			Flood 41°	1 494	62	3 068	LBXS10-930-FL
			Wide flood 58°	1 494	62	1 904	LBXS10-930-WF
			Wall washer	627	26	470	LBXS10-930-WW
			Wall washer LGC (longitudinal glare control)	528	22	520	LBXS10-930-WL

Use multiplier table for other CCT and CRI output data. Efficacy based on IESNA LM-79 test reports. Visit iguzzini.com/us for complete photometric data.


Medium 24° (3000K, 90CRI)




Flood 41° (3000K, 90CRI)




Wide flood 58° (3000K, 90CRI)



Wall washer (3000K, 90CRI)



Wall washer LGC (3000K, 90CRI)



CCT options	2700K	3000K	3500K	4000K
CRI options	90CRI	90CRI	90CRI	90CRI
Multiplier	0.94	1	1	1.19

LINEAR SMALL LASER BLADE XS

SURFACE - INLINE SYSTEM

Type:

Project:


SPECIFICATION SHEET

Page: 7 of 7

PHOTOMETRIC DATA

Photometric data for one laser blade module

LBXS15




MD
FL
WF

CCT (K)	CRI	LOAD (W)	OPTIC	LUMENS (lm)	EFFICACY (lm / W)	MAX CANDELA (cd)	MODELS
3000K	90	34.5W	Medium 24°	2 133	61	9 855	LBXS15-930-MD
			Flood 41°	2 241	64	4 603	LBXS15-930-FL
			Wide flood 58°	2 241	64	2 856	LBXS15-930-WF
			Wall washer	912	26	684	LBXS15-930-WW
			Wall washer LGC (longitudinal glare control)	768	22	757	LBXS15-930-WL


Use multiplier table for other CCT and CRI output data. Efficacy based on IESNA LM-79 test reports. Visit iguzzini.com/us for complete photometric data.

Medium 24° (3000K, 90CRI)




Center beam fc	Beam width ft
2ft 2 464	0.9
4ft 616	1.8
6ft 274	2.7
8ft 154	3.5
10ft 98.6	4.4
12ft 68.4	5.3

Flood 41° (3000K, 90CRI)




Center beam fc	Beam width ft
2ft 1 138	1.5
4ft 285	3.0
6ft 126	4.6
8ft 71.1	6.1
10ft 45.5	7.6
12ft 31.6	9.1

Wide flood 58° (3000K, 90CRI)




Center beam fc	Beam width ft
2ft 705	2.2
4ft 176	4.4
6ft 78.4	6.6
8ft 44.1	8.8
10ft 28.2	11.0
12ft 19.6	13.2

Wall washer (3000K, 90CRI)



Wall washer LGC (3000K, 90CRI)



CCT options	2700K	3000K	3500K	4000K
CRI options	90CRI	90CRI	90CRI	90CRI
Multiplier	0.94	1	1	1.21